



NTN Bearing Driveshaft do Brasil



140 mm x 250 mm x 42 mm 140 mm x 250 mm
x 42 mm SKF NU 228 ECML thrust ball bearings

Bearing No. NU 228 ECML

NU 228 ECML Bearing 2D drawings and 3D CAD models

Size	250x140x42 mm
Bore Diameter	250 mm
Outer Diameter	140 mm
Width	42 mm
d	140 mm
D	250 mm
B	42 mm
D ₁	216.7 mm
F	169 mm
r _{1,2} - min.	3 mm
r _{3,4} - min.	3 mm
s	2.5 mm
d _a - min.	154 mm
d _a - max.	165 mm
d _b - min.	172 mm
D _a - max.	235 mm
r _a - max.	2.5 mm
r _b - max.	2.5 mm
Basic dynamic load rating - C	450 kN
Basic static load rating - C ₀	510 kN
Fatigue load limit - P _u	57 kN
Reference speed	2800 r/min
Limiting speed	4800 r/min
Calculation factor - k _r	0.23



NTN Bearing Driveshaft do Brasil

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	9.445
EAN	7316570321777
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	140MM Bore; Straight Bore Profile; 250MM Outside Diameter; 42MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing



NTN Bearing Driveshaft do Brasil

Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 228 ECML
Weight / LBS	20.803
Outside Diameter	9.843 Inch 250 Millimeter
Bore	5.512 Inch 140 Millimeter
Width	1.654 Inch 42 Millimeter
bore diameter:	140 mm
static load capacity:	510 kN
outside diameter:	250 mm
maximum rpm:	4800 rpm
overall width:	42 mm
bearing material:	Steel
flanges:	(2) Flanges on outer Ring, Flangeless Inner Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
operating temperature range:	Maximum 302 ° F
series:	NU
dynamic load capacity:	450 kn
manufacturer upc number:	7316570321777
D_1	216.7 mm
$r_{1,2}$ min.	3 mm
$r_{3,4}$ min.	3 mm
s max.	2.5 mm
d_a min.	154 mm
d_a max.	165 mm
d_b min.	172 mm
D_a max.	235 mm
r_a max.	2.5 mm



NTN Bearing Driveshaft do Brasil

r_b max.	2.5 mm
Basic dynamic load rating C	450 kN
Basic static load rating C_0	510 kN
Fatigue load limit P_u	57 kN
Calculation factor k_r	0.23
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	9.24 kg