



NTN Bearing Driveshaft do Brasil



45 mm x 85 mm x 19 mm 45 mm x 85 mm x 19 mm SKF NU 209 ECJ thrust ball bearings

Bearing No. NU 209 ECJ

NU 209 ECJ Bearing 2D drawings and 3D CAD models

Size	85x45x19 mm
Bore Diameter	85 mm
Outer Diameter	45 mm
Width	19 mm
d	45 mm
D	85 mm
B	19 mm
D ₁	72.4 mm
F	54.5 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	1.1 mm
s	1.2 mm
d _a - min.	52 mm
d _a - max.	53 mm
d _b - min.	56 mm
D _a - max.	77.6 mm
r _a - max.	1 mm
r _b - max.	1 mm
Basic dynamic load rating - C	69.5 kN
Basic static load rating - C ₀	64 kN
Fatigue load limit - P _u	8.2 kN
Reference speed	9000 r/min
Limiting speed	9500 r/min
Calculation factor - k _r	0.15



NTN Bearing Driveshaft do Brasil

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.449
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	45MM Bore; Straight Bore Profile; 85MM Outside Diameter; 19MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Inter
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com



NTN Bearing Driveshaft do Brasil

Manufacturer Item Number	NU 209 ECJ
Weight / LBS	0.99
Bore	1.772 Inch 45 Millimeter
Width	0.748 Inch 19 Millimeter
Outside Diameter	3.346 Inch 85 Millimeter
bore diameter:	45 mm
static load capacity:	64 kN
outside diameter:	85 mm
precision rating:	Not Rated
overall width:	19 mm
maximum rpm:	9500 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Steel
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C0
closure type:	Open
ring separation:	Separable Ring
outer ring width:	19 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	1 mm
dynamic load capacity:	69.5 kN
series:	NU2
D ₁	72.4 mm
r _{1,2} min.	1.1 mm
r _{3,4} min.	1.1 mm
s max.	1.2 mm
d _a min.	52 mm
d _a max.	53 mm



NTN Bearing Driveshaft do Brasil

d_b min.	56 mm
D_a max.	77.6 mm
r_a max.	1 mm
r_b max.	1 mm
Basic dynamic load rating C	69.5 kN
Basic static load rating C_0	64 kN
Fatigue load limit P_u	8.15 kN
Calculation factor k_r	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	0.43 kg